

## Wall Mounted Eye Wash Stations



Product Code: S0420

Our basic wall mounted eye wash station can be used in factories, chemical plants, foundries, workshops, and any workplace that requires emergency eye wash facilities. This emergency eye wash unit is wall-mounted for stability, while the compact dimensions mean that it can be installed almost anywhere without causing undue obstruction.

This wall mounted eye wash fountain is constructed from hardwearing stainless steel and ABS plastic in bright yellow for visibility in emergency situations. Once activated via the large, easy to use push paddle, the unit can be operated hands free. The spray nozzles also come with built-in dust covers and water filters to prevent contamination.

Each wall mounted eye wash unit comes with a 32mm waste and a weekly inspection tag to encourage regular functional testing. In order to comply with the ANSI regulations, the unit must be mounted no lower than 838mm and no higher than 1143mm from the floor.

### Delivery

From stock 1 to 2 working days delivery time

Orders placed before 11.30am will be despatched for delivery next working day, or two working days if ordered after 11.30am

### Tech specs

Bowl diameter: 300mm

Bowl material: ABS plastic, yellow

Waste fitting: 32mm, chrome-plated brass

Water pressure: 2.07 - 6.21 bar

Flow Rate: 23.47 litres per minute

Ball valve: 1/2" chrome plated brass stay-open ball valve with 50 mesh inline strainer, brass 1/2" male BSP connector

Handle: stainless steel push handle

Spray heads: yellow ABS plastic spray heads with flip open covers, internal flow controls and filters

Bracket: yellow coated 3mm galvanised steel wall bracket

### Extras

Our wall mounted emergency eyewash fountains are supplied without traps. You can choose the following:

[32mm chrome-plated brass trap with waste pipe and flange](#)

### What is ANSI compliance?

The ANSI (or [American National Standards Institute](https://www.anstd.org/)) is a nonprofit organisation that administers standards for products, processes and systems in the United States and around the world.

With regards to safety eye washing, the ANSI sets standards for water temperature and flow rate, as well as location and maintenance requirements. Our safety wall mounted eye washing pods conform to ANSI Z358.1.

### Related products

We also sell [wall mounted eye wash fountains with stainless steel bowls](#) for increased durability, as well as [portable eye wash stations](#) for use in remote areas without access to clean water.

In addition to eye wash fountains, we also provide a range of [safety showers](#), which come in [wall mounted](#), [ceiling mounted](#) and [freestanding models](#).

**\*\*All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.  
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.\*\***